

1341 West Mockingbird Lane • Dallas, Texas 75247 • 972 647 6700 • www txi com

MATERIAL SAFETY DATA SHEET

SECTION 1 - IDENTITY

Name

TXI OPERATIONS, LP

Emergency Telephone Number

(972) 647-6700

Common Name (used on label)

MASONRY CEMENT

Chemical Name

DOES NOT APPLY

Trade Name & Synonyms

MASONRY CEMENT, TXI MASONS MIX TYPE S-N

3/6/3

80

NANCY GARNETT

Person Responsible for Preparation

Address

1341 W. MOCKINGBIRD LANE, DALLAS, TEXAS 75247

Date

NOVEMBER 1998

Chemical Pamily DOES NOT APPLY

Formula

A HETEROGENEOUS MIXTURE OF BASIC CALCIUM SILICATES.

ALUMINATES AND FERRITES TOGETHER WITH CALCIUM CARBONATE AND SMALL IMPURITIES OF MAGNESIA. CHROMIUM AND COMPLEX ALKALI METAL COMPOUNDS.

SECTION 2 - HAZARDOUS INGREDIENTS				
Hazardous Component	CAS#	% Typical	TLV (Unita)	PEL (Units)
PORTLAND CEMENT LIMESTONE QUARTZ	65997-15-1 1317-65-3 14808-60-7	55 - 70 30 - 40 < 2	10 mg/m³ 10 mg/m³ 0.1 mg/m³*	5 mg/m³• 10 mg/m³ 0.1 mg/m³•
GYPSUM	13397-24-5	2 - 3	10 mg/m³	5 mg/m ⁵ *

* Respurable portion.

PEL: Permissible Exposure Limit established by the Occupational Safety and Health Administration (OSHA).

TLV: Threshold Limit Value established by the American Conference of Governmental Industrial Hygienists (ACGIH).

SECTION 3 - PHYSICAL DATA

Boiling Point

DOES NOT APPLY

Percent Volatile by Volume

Percent Soluble in Water SLIGHT (0.1 - 1.0%)

Appearance and Odor

FINE, GRAY POWDER, NO ODOR

Specific Gravity ($H_1O = 1$)

2.80 - 3.00

Vapor Density (Air = 1)

DOES NOT APPLY

Reactivity in Water

WILL NOT EVOLVE FLAMMABLE OR TOXIC GASES

Vapor Pressure (mm = Hg)

DOES NOT APPLY

Evaporation Rate (n=Butyl Acetate)

DOES NOT APPLY

Hazardous Material Information System Identifier (HMIS)

HEALTH = 2 FLAMMABILITY = 0

REACTIVITY = 1

PERSONAL PROTECTION = X

SECTION 4 - FIRE AND EXPLOSION DATA

Plash Point WILL NOT IGNITE Extinguishing Media DOES NOT APPLY

Unusual Fire and Explosion Hazards

NONE

Special Fire Fighting Procedures

NONE

Flammable Limits in Air (% by Volume)

Lower DOES NOT APPLY Upper DOES NOT APPLY

Auto Ignition Temperature

DOES NOT APPLY

SECTION 5 - HEALTH INFORMATION

Signs and Symptoms of Exposure - (1) Acute Overexposure

1. 1. 2. 2. 1

TERTITATION OF SKIN, EYES, OR NASAL PASSAGES FROM ALKALLIN PORTLAND CEMENT. WHEN WET, CONTACT WITH THE SKIN OR EYES MAY RESULT IN IRRITATION OR BURNS.

Signs and Symptoms of Exposure - (2) Chronic Overexposure

CEMENT DUST CAN CAUSE INFLAMMATION OF THE LINING TISSUE OF THE INTERIOR OF THE NOSE AND INFLAMMATION OF THE CORNEA. HYPERSENSITIVE INDIVIDUALS MAY DEVELOP ALLERGIC DERMATITIS. EXCESSIVE EXPOSURE TO CRYSTALLINE QUARTZ BY BREATHING DUST OVER AN EXTENDED PERIOD OF TIME MAY RESULT IN THE DEVELOPMENT OF PULMONARY DISEASES INCLUDING PNEUMOCONIOSIS AND SILICOSIS, WHICH COULD EVENTUALLY LEAD TO LUNG CANCER.

Medical Conditions Generally Aggravated by Expos

RESPIRATORY DISORDERS OR DISEASES, DERMATTIS, OR OTHER SKIN DISORDERS MAY BE AGGRAVATED BY EXPOSURE.

Chemical/Component Listed as Carcinogen

-31 B

QUARTZ

Other Exposure Limits

Emergency & Pirst Aide Procedures for Indicated Routes of Entry

INHALATION: REMOVE FROM EXPOSURE. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CONSULT A PHYSICIAN.

EYE CONTACT: IMMEDIATELY FLUSH EYES WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN.

SKIN CONTACT: IMMEDIATELY WASH SKIN THOROUGHLY WITH SOAP AND WATER.

SECTION 6: - REACTIVITY DATA

Stability

Conditions to Avoid

STABLE Incompatibility (Materials to Avoid)

MATERIAL IS HIGHLY ALKALINE. CONTACT WITH ACIDS WILL PRODUCE A VIOLENT, EXOTHERMIC REACTION AND MAY EVOLVE TOXIC GASES OR VAPORS, DEPENDING UPON THE ACID INVOLVED.

Hazardous Decomposition or Combustion Products

4. 17 85

DOES NOT APPLY

Hazardous Polymenzation WILL NOT OCCUR

Conditions to Avoid DOES NOT APPLY

DOES NOT APPLY

Steps to be Taken in Case Material is Leaked or Spilled

CLEAN-UP OF SPILLS MAY REQUIRE PERSONAL PROTECTIVE EQUIPMENT TO PREVENT DUST EXPOSURES AND PROTECT AGAINST ALKALI BURNS OR IRRITATION. SEE SECTION 8.

SECTION 7 - SPILL OR LEAK PROCEDURES

Waste Disposal Method

IF THIS MATERIAL, AS PACKAGED, BECOMES A WASTE, IT DOES NOT MEET THE CRITERIA FOR A HAZARDOUS WASTE AS DEFINED BY THE ENVIRONMENTAL PROTECTION AGENCY UNDER THE AUTHORITY OF THE RESOURCE CONSERVATION AND RECOVERY ACT (40CFR 261). DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

* - - - - - - - SECTION * 8 - PERSONAL PROTECTION INFORMATION & 5

Respiratory Protection

NIOSH/MSHA APPROVED FOR PROTECTION AGAINST NUISANCE DUSTS.

Ventilation

GENERAL OR LOCAL PYHALIST TO MAINTAIN PYPOSURE BRLOW TO VIPEL

Eye Protection

RUBBER, PVC, NEOPRENE OR OTHER IMPERVIOUS MATERIAL.

GOGGLES

Other Protective Clothing or Equipment

RUBBER HIGH TOP BOOTS, BARRIER CREAMS, ARM SLEEVES AND APRONS MAY BE USED, WHEN NECESSARY, TO PREVENT SKIN CONTACT.

SECTION 9 - SPECIAL PRECAUTIONS

Precautions to be Taken in Handling & Storing

SHOULD BE STORED IN A MANNER TO PREVENT CONTACT WITH STRONG ACIDS. CONTACT WITH WATER SHOULD BE AVOIDED TO PRESERVE PRODUCT

Other Precautions

NONE

TX1003